


FEATURES:

- Through - wiring via sealed snap-in connectors.
- IP 67 rated for use in dry, damp or wet locations.
- Addressable per module.
- Projected lifetime ≥ 80000 hours
- Operating temperature $-35 \sim 60^{\circ}\text{C}$
- 5 year limited warranty
- Round, flat UV stable and impact resistant PMMA diffusers
- No dimming, On/off or DMX, DALI or 0-10V control system.
- Mounting profile with end caps for additional protection.

Model	L19RGB
Chip Brand	CREE/Epistar
LED Source	3SMD RGB
Color Resolution	255/65536
Beam Angle	120°
Pixel Pitch	200mm
Housing	PC
Housing Color	Transparent
Optical Lens	Flat Transparent
Weight	3g
Certification	ETL, CE, RoHS
Operating Voltage	DC12V
Power Consumption	0.72W
Control	DMX
Ingress Protection	IP67
Fire Protection Rating	UL94-V0
Operating Temperature	$-35 \sim 60^{\circ}\text{C}$
Storage Temperature	$-40 \sim 70^{\circ}\text{C}$
Lifespan	≥ 80000 h

LED 3pcs	Red 620nm-6*800mcd
DC12V	Green 520nm-6*1200mcd
0.72W	Blue 465nm-6*430mcd
TTL	RGB
Light Intensity: 12.01cd	
V 0°/105.6°	H 0°/105.9°
Distribution Curve Flux	



Illumination Icon

