

FEATURES:


- Through - wiring via sealed snap-in connectors.
- IP 66 rated for use in dry, damp or wet locations.
- Addressable per module.
- Projected lifetime ≥ 80000 hours
- Operating temperature $-35 \sim 60^{\circ}\text{C}$
- 5 year limited warranty
- Round, flat UV stable and impact resistant PMMA diffusers
- No dimming, On/off or DMX, DALI or 0-10V control system.
- Mounting profile with end caps for additional protection.

Model	L28RGB
Chip Brand	CREE/Epistar 96
LED Source	SMD RGB
Color Resolution	16bit
Beam Angle	120°
Housing	Aluminum
Housing Color	Silver
Cover	PC
Weight	1.2kg
Certification	ETL、CE、ROHS
Operating Voltage	DC24V
Power Consumption	16W
Control	DMX
Ingress Protection	IP66
Fire Protection Rating	UL94-V0
Operating Temperature	$-35 \sim 60^{\circ}\text{C}$
Storage Temperature	$-40 \sim 70^{\circ}\text{C}$
Lifespan	≥ 80000 h
CRI	≥ 80

LED 96PCS Red620nm-6*800mcd
 DC24V Green520nm-6*1200mcd
 24W Blue465nm-6*430mcd
 DMX RGB

Light Intensity: 154.2cd
 V 0°/134° H 0°/113°

Distribution Curve Flux



Illumination Icon

